

# K-FLEX® COLOR SYSTEM



## K-FLEX® COLOR SYSTEM

- ▶ Colour finished insulation
- ▶ Aesthetic design
- ▶ Flexible and easy of application
- ▶ Colour coding for different services
- ▶ UV protection


Site



Video




TECHNICAL DATA



K-FLEX® COLOR SYSTEM (FINISHING ONLY) ▶ TECHNICAL DATA		
Property	Value	Test method
WOM 2000 hours	No significant alteration	DIN 53231
Humidistat 800 hours	Elasticity remains the same	DIN 53231
Adhesion 24 hours after humidistat	Adhesion remains intact	
UV 2000 hours QUV/SE	No blistering, no separation, no significant alterations	
Wash H2O	No alterations	
Wash H2O plus soap for hands	No alterations	
Test with solution 1	Elasticity and adhesion remain the same	DIN 53160/UAN-D1235/01
Test with solution 2	Elasticity and adhesion remain the same	DIN 53160/UAN-D1235/01
Immersion in water 60 °C 800 hours	No blistering, no separation	
Caustic soda contact to 5% 2 hours	No alterations	
Fire rating (with K-FLEX® ST)	Sheet: Euroclass C-s3, d0 Tube: Euroclass C <sub>L</sub> -s3, d0	EN13501-1 EN13501-1
Fire rating (facing only)	Class 0	BS 476 Part 6/7

K-FLEX® reserves the right to change data and technical requirements without notice.

GENERAL INFORMATION



K-FLEX® COLOR SYSTEM  
TUBES

Insulation tube with a protective factory-applied coating. The thin layer of colour coating offers protection against UV rays and facilitates cleaning and maintenance of the insulation. Flexible, easy to work with and install.



K-FLEX® COLOR SYSTEM  
SHEETS

K-FLEX® COLOR SYSTEM sheets are available in standard or self-seal. They are designed for use with conduits, ventilation ducts and large pipes. Their flexibility and ease of processing make this material especially suitable for awkward configurations and trims.



K-FLEX® COLOR SYSTEM  
ACCESSORIES

K-FLEX® offers a range of accessories especially for use with K-FLEX® COLOR SYSTEM. In addition to the standard pieces, curves, couplings and supports, adhesive tapes and coloured paints are available for re-touching and repairs.

K-FLEX® COLOR SYSTEM ▶ RANGE			
	Length	Thicknesses	Diameters
K-FLEX® COLOR - Tubes	2 m	9-13-19-25-32 mm	from 10 to 54 mm
K-FLEX® COLOR - Tubes	1 m	9-13-19-25-32 mm	from 57 to 160 mm
	Thicknesses		Height
K-FLEX® COLOR - Sheets	6-10-13-19-25-32-40-50 mm		1000/1500 mm
K-FLEX® COLOR - Adhesive sheets	6-10-13-19-25-32-40-50 mm		1000/1500 mm

COLOR RANGE


Stock colour range and product codes

☐ RAL 7035 grey - Colour code **G0**   ☐ RAL 9002 white - Colour code **G1**   ☒ RAL 9011 black - Colour code **N0**

For the minimum order quantity per colour listed below, contact your sales office

☒ RAL 5012 blue - Colour code **B0**   ☒ RAL 6032 green - Colour code **V0**   ☒ RAL 3000 red - Colour code **R0**

ACCESSORIES



K-FLEX® COLOR preformed "T" fittings   K-FLEX® COLOR preformed elbows   K-FLEX® COLOR pipe support   K-FLEX® COLOR pipe support with collar   K-FLEX® COLOR paint   K-FLEX® COLOR anticonsonation tape



PROJECTS

Germany

